

HNT-7000 HUVITZ TONOMETER





HNT-7000 HUVITZ TONOMETER

- Full auto tracking, focusing, shooting
- Smart puffing control system
- Compensation of corneal thickness function
- 5.7" touch & tilting color TFT LCD
- Data interface with PC
- Safety stop function
- Motorized chinrest

SPECIFICATIONS

Type	Non Contact type
Measurable range	0 to 60mmHg
Measuring increment	1mmHg
Working distance	11mm from the front of nozzle
Alignment mode	Full Auto (R/L Shift, Alignment, Focusing, Puffing) Semi Auto (Alignment, Focusing, Puffing) Manual
Interface	RS232C
Power saving system	Available
Display	5.7-inch Color TFT LCD (0~90° Tilttable)
Printer	Thermal line printer
Power supply	AC100-240V, 50 / 60Hz
Power consumption	80VA
Operating range	Front / Back : 40mm Left / Right : 90mm Up / Down : 30mm
Dimensions	294(W) x 510(D) x 462(H)mm
Weight	20.5kg (45.2 lbs.)
Accessories	Main unit 1 ea, Chin rest paper 1 pack Printing paper 1 roll, Power cable 1 ea Dust cover 1 ea, Operation Manual 1 ea

Designs and details can be changed without prior notice for the purposes of improvement.

Huvitz

Huvitz Building 689-3, Geumjeong-dong
Gunpo-si, Gyeonggi-do, 435-862, Korea

Tel : +82-31-442-8868

Fax : +82-31-477-8617

http://www.huvitz.com

Distributed by